

Well Name: UNIVERSITY 10 2702H

API/UWI 4238338227		Surface Legal Location S 27, BLK 10, ULS		Lease Number 756381		State/Province Texas	
Spud Date 8/24/2013 19:30		Rig Release Date		KB-Ground Distance (ft) 25.00		KB-Casing Flange Distance (ft)	
Weather Partly cloudy		Temperature (°F) 59.0		Road Condition Good		Hole Condition	
Operations at Report Time Wait on Daylight				Operations Next Report Period Move rig & rig up			
Operations Summary R/D Trinidad #101, PJSM W/Permain Trucking, Crane crews, Rig manager & Rig Crews, begin rig down & move W/Trucks & cranes, Move & set mats, mud tanks, mud pumps, shakers, gas buster & choke manifold, move numerous misc loads							
Remarks 50% rigged down, 25% moved							
Mud Checks							
Time	Type	Depth (ftKB)	Density (lb/gal)	Vis (s/qt)	PV Calc (cP)	YP Calc (lb/100ft²)	
Gel (10s) (lb/100ft²)	Gel (10m) (lb/100ft²)	Gel (30m) (lb/100ft²)	Filtrate (mL/30min)	Filter Cake (1/32")	pH	Solids (%)	
MBT (lb/bbl)	Percent Oil (%)	Percent Water (%)	Chlorides (mg/L)	Calcium (mg/L)	Potassium (mg/L)	Electric Stab (V)	
Drill Strings							
BHA #<stringno>, <des>							
Bit Run	Drill Bit			IADC Bit Dull		TFA (incl Noz) (in²)	
Nozzles (1/32")				String Length (ft)	String Wt (1000lbf)	BHA ROP (ft/hr)	
Drilling Parameters							
Wellbore	Start Depth (ftKB)	End Depth (ftKB)	Cum Depth (ft)	Drilling Time (hr)	Cum Drill Time (hr)	Int ROP (ft/hr)	Flow Rate (gpm)
WOB (1000lbf)	RPM (rpm)	SPP (psi)	Drill Str Wt (100...	PU Str Wt (1000...	SO Str Wt (1000...	Drilling Torque	Off Bottom Torque
Q Gas Inj (ft³/min)	T Inj (°F)	P BH Ann (psi)	T BH (°F)	P Surf Annulus (...)	T Surf Annulus (...)	Q Liq Return (gp...	Q Gas Return (ft³...

Start Depth (ftKB) 0.0		End Depth (ftKB) 0.0	
Target Depth (ftKB) 16,340.0		Days LTI (days)	
Last Casing String SURFACE 1, 814.0ftKB			
Daily Contacts			
Job Contact		Mobile	
Pete Rockholt, Consultant		(806) 445-5603	
Rigs			
Contractor Trinidad Drilling		Rig Number 101	
Rig Supervisor Corey Howell, Rig Manager		Phone Mobile 334 449 7075	
Mud Pumps			
# 1 , National Supply , 12-P-160			
Pump Rating (hp) 1,000.0	Rod Diameter (in)	Stroke (in) 12.01	
Liner Size (in)		Vol/Stk OR (bbl/stk)	
P (psi)	Slow Spd	Strokes (sp...	Eff (%)
# 2 , National Supply , 12-P-160			
Pump Rating (hp) 1,000.0	Rod Diameter (in)	Stroke (in) 12.01	
Liner Size (in)		Vol/Stk OR (bbl/stk)	
P (psi)	Slow Spd	Strokes (sp...	Eff (%)
Survey Data (last 5 records)			
MD (ftKB)	Incl (°)	Azm (°)	TVD (ftKB)