

Well Name: UNIVERSITY 10 2702H

API/UWI 4238338227	Surface Legal Location S 27, BLK 10, ULS	Lease Number 756381	State/Province Texas				
Spud Date 8/24/2013 19:30	Rig Release Date	KB-Ground Distance (ft) 25.00	KB-Casing Flange Distance (ft)				
Weather Clear	Temperature (°F) 92.0	Road Condition Good	Hole Condition Good				
Operations at Report Time Jarring fish out of hole @ 1370'		Operations Next Report Period Jar fish out of hole					
Operations Summary Continue jarring fish out of hole f/ 5997' to 3002", lost string weight, TOO H w/o fish, grapple came off fish, m/u new fishing bha, replace grapple and jars, TIH to 3002' and tag fish, latch onto fish and begin jarring fish out of hole to 1370'							
Remarks							
Mud Checks							
Time 06:00	Type Oil Base	Depth (ftKB) 15,639.0	Density (lb/gal) 9.50	Vis (s/qt) 62	PV Calc (cP) 16.0	YP Calc (lb/100ft²) 13.000	
Gel (10s) (lb/100ft²) 10.000	Gel (10m) (lb/100ft²) 13.000	Gel (30m) (lb/100ft²) 17.000	Filtrate (mL/30min)	Filter Cake (1/32")	pH	Solids (%) 10.0	
MBT (lb/bbl)	Percent Oil (%) 77.0	Percent Water (%) 23.0	Chlorides (mg/L) 40,000.000	Calcium (mg/L) 27,000.000	Potassium (mg/L)	Electric Stab (V) 580.0	
Drill Strings							
BHA #<stringno>, <des>							
Bit Run	Drill Bit		IADC Bit Dull		TFA (incl Noz) (in²)		
Nozzles (1/32")				String Length (ft)	String Wt (1000lbf)	BHA ROP (ft/hr)	
Drilling Parameters							
Wellbore	Start Depth (ftKB)	End Depth (ftKB)	Cum Depth (ft)	Drilling Time (hr)	Cum Drill Time (hr)	Int ROP (ft/hr)	Flow Rate (gpm)
WOB (1000lbf)	RPM (rpm)	SPP (psi)	Drill Str Wt (100...	PU Str Wt (1000...	SO Str Wt (1000...	Drilling Torque	Off Bottom Torque
Q Gas Inj (ft³/min)	T Inj (°F)	P BH Ann (psi)	T BH (°F)	P Surf Annulus (...)	T Surf Annulus (...)	Q Liq Return (gp...	Q Gas Return (ft³...

Start Depth (ftKB) 15,639.0	End Depth (ftKB) 15,639.0
Target Depth (ftKB) 16,340.0	Days LTI (days)
Last Casing String Intermediate, 7,524.0ftKB	
Daily Contacts	
Job Contact	Mobile
Stoney Marquis, Consultant	(940) 594-3028
Rigs	
Contractor Trinidad Drilling	Rig Number 101
Rig Supervisor Tim Sepulvado, Rig Manager	Phone Mobile (318) 602-8578
Mud Pumps	
# 1 , National Supply , 12-P-160	
Pump Rating (hp) 1,000.0	Rod Diameter (in) Stroke (in) 12.01
Liner Size (in) 6	Vol/Stk OR (bbl/stk) 0.100
P (psi) 400.0	Slow Spd Yes
	Strokes (sp... 30
	Eff (%) 95
# 2 , National Supply , 12-P-160	
Pump Rating (hp) 1,000.0	Rod Diameter (in) Stroke (in) 12.01
Liner Size (in) 6	Vol/Stk OR (bbl/stk) 0.100
P (psi) 500.0	Slow Spd Yes
	Strokes (sp... 40
	Eff (%) 95
Survey Data (last 5 records)	
MD (ftKB)	Incl (°)
	Azm (°)
	TVD (ftKB)