



Texas Commission
on Environmental Quality
Surface Casing Program

DEPTH OF USABLE-QUALITY GROUND WATER TO BE PROTECTED

Date **January 25, 2011**

TCEQ File No.: SC- **14049**

***** EXPEDITED APPLICATION *****

API Number **00300000**

Attention: **DAWN RICHARDSON**

RRC Lease No. **000000**

SC_748011_00300000_000000_14049.pdf

**SANDRIDGE E&P LLC
123 ROBERT S KERR
OKLAHOMA CITY OK 73102**

P-5# 748011

--Measured--

345 ft FEL

1560 ft FNL

MRL: SECTION

Digital Map Location:

X-coord/Long	368259
Y-coord/Lat	217315
Datum	27
Zone	NC

County **ANDREWS**

Lease & Well No. **UNIVERISTY ATP #16**

Purpose **ND**

Location **SUR-UL, BLK-11, SEC-15, -- [TD=7999] , [RRC 8] ,**

To protect usable-quality ground water at this location, the Texas Commission on Environmental Quality recommends:

The interval from the land surface to a depth of 300 feet and the ZONE from 1000 feet to 1375 feet must be protected.

Note: Unless stated otherwise, this recommendation is intended to apply only to the subject well and not for area-wide use. Approval of the well completion methods for protection of this groundwater falls under the jurisdiction of the Railroad Commission of Texas. **This recommendation is intended for normal drilling, production, and plugging operations only. It does not apply to saltwater disposal operation into a nonproductive zone (RRC Form W-14).**


If you have any questions, please contact us at 512-239-0515, sc@tceq.state.tx.us, or by mail MC-151.

Sincerely,

[Signature area]

Jack M. Oswalt, P.G.

GEOLOGIST SEAL



Geologist, Surface Casing Team
Waste Permits Division

The seal appearing on this document was authorized by Jack M. Oswalt on 1/25/2011
Note: Alteration of this electronic document will invalidate the digital signature.